



www.preet.co

FARMING WITH PASSION

UNMATCHED POWER & STYLE

PREET 6049 4WD

More Power in Less Fuel Consumption
Low Maintenance Cost



FEATURES



Bonnet Lock
with Key



Electronic
Meter



Mobile Charger
Point



Power
Steering



Big Air
Cleaner



Aero Dynamic
Bonnet



Oil Immersed
Brake



Multi Speed PTO
& Reverse PTO

PREET 6049
4 WHEEL DRIVE

PREET Tractor - 6049 4WD

Technical Specifications

| ENGINE | | | | | | |
|-----------------------|------------------------------|--------|------|---------|--------|------|
| Model / Make | PREET - 6049 | | | | | |
| HP Category | 60 | | | | | |
| Type | Four Stroke DI | | | | | |
| No. of Cylinders | 4 Cylinder, Vertical Inline | | | | | |
| Bore / Stroke (mm) | 105 / 118 | | | | | |
| Rated Engine (RPM) | 2200 | | | | | |
| Displacement (cc) | 4087 | | | | | |
| Fuel Pump | Multicylinder Inline (BOSCH) | | | | | |
| Air Cleaner Type | Dry | | | | | |
| Cooling System | Water Cooled | | | | | |
| CLUTCH | | | | | | |
| Type | Heavy Duty DC | | | | | |
| Plate Size | Dia 280 mm | | | | | |
| TRANSMISSION | | | | | | |
| Gear Box | 12F + 12R Synchro Mesh | | | | | |
| ROAD SPEED KM/hr | FORWARD | | | REVERSE | | |
| Gear | HIGH | MEDIUM | LOW | HIGH | MEDIUM | LOW |
| 1 | 10.35 | 3.90 | 1.53 | 8.68 | 3.27 | 1.29 |
| 2 | 15.33 | 5.78 | 2.27 | 12.85 | 4.84 | 1.91 |
| 3 | 22.43 | 8.45 | 3.33 | 18.81 | 7.09 | 2.79 |
| 4 | 31.52 | 11.88 | 4.68 | 26.43 | 9.96 | 3.92 |
| HYDRAULIC SYSTEM | | | | | | |
| Type | 2 Lever, ADDC | | | | | |
| Hydraulic Pump | Gear Type | | | | | |
| Linkage | TPL Category-II | | | | | |
| Lifting Capacity (kg) | 2400 | | | | | |
| STEERING | | | | | | |
| Type | Power Steering | | | | | |

| POWER TAKE OFF | |
|---------------------------|-------------------------|
| Type | Dual Speed Live |
| Splines | 6 |
| PTO / Speed | 540 and 1000 |
| CAPACITIES (LITRES) | |
| Fuel Tank | 67 |
| Engine Sump | 11 |
| Cooling System | 9.5 |
| Transmission & Hydraulic | 35 |
| Steering System | 2 |
| ELECTRICAL INSTALLATION | |
| Battery | 12V, 100Ah |
| Alternator | 12V, 42A |
| Starter Motor | 12V, 2.7 KW |
| MIN. TURNING RADIUS | |
| Without Brakes (m) | 4 |
| TYRE SIZE | |
| Front | 9.5 - 24 |
| Rear | 16.9 - 28 |
| Weight (Kg.) | 2530 |
| FRONT DRIVE AXLE | |
| Differential | Limited Slip |
| Bevel Ratio | 1:2.133 |
| Hub Ratio | 1:6 |
| Total Ratio | 1:12.8 |
| Diff. Oil Capacity (Ltr.) | 5.5±10% |
| Hub Oil Capacity (Ltr.) | 0.6±15% each side |
| BRAKES | |
| Type | Multi Disc Oil Immersed |

Note : As per our policy is that of continuous development, specifications may change without any prior notice. For further details contact your nearest dealer.

Authorised Dealer :

PREET TRACTORS PVT. LTD.

Patiala Road, NABHA-147 201 (Pb.) INDIA. Tel.: 01765-220400, 222609

Toll Free : 1800-4190349 Email: info@preet.co | sales@preet.co

Visit us at : www.preet.co