Delivering Ultimate Mechanical Perfection.





Specially Designed for:





















www.preet.co

Paddy

Maize

Red Gram

Soyabean

Sunflower

Mustard

Grams

Arhar

Moong

Ready to Thrill with eye catching Features :



Small Cutter Bar suitable for small fields.




Comfortable cushioned driver seat with adjustable height




Heavy duty gearbox




Best Paint quality



Well designed crop feeding mechanism



Large sieve area for optimum grain cleaning



Long length Straw Walker for complete exit of straw



Broader Canopy Providing Extra Cover to the Operator Area Long Distance Focus Light Small Turning Radius



Large grain tank capacity enables long working hours with minimum interruption



Easy to open elevators for maintenance & services




Heavy duty, long durable and robust structure makes our machine to withstand against any impact



Oil-immersed brake designed for use on a drive heavy machines



Easy to Move with Less Force Hydraulic Power Steering



Stainless steel sheet used for long life of auger casing



Stainless steel sheet used for long life of parts which are subjected to more wearing like elevators
USE UCF bearing is widely appreciated for durability and long serviceability

PREET 649 SELF PROPELLED MAIZE COMBINE HARVESTER

TECHNICAL SPECIFICATIONS

A.	ENGINE					
	Model	ALUW-04D				
	Power	76 PS at 2200 RPM				
	No. of Cylinders	4				
	Air Cleaner	Dry Type				
	Cooling System	Water Cooled				
B.	CLUTCH					
	Type of Clutch	Single, Heavy Duty Dry Clutch				
	Dia	310 mm				
C.	TRANSMISSION					
	No. of Gears	3 Forward, 1 Reverse @ 1800 RPM				
	Gear Speed (km/hr)					
	Forward	L 2 4.7 11.5		Н		
	1st Gear			3.2		
	2nd Gear			7		
	3rd Gear			17.5		
	Reverse	5.2			8	
D.	CUTTER BAR MECHANISM					
	Cutter Bar Width	3430 mm (11.25 Feet)				
	Cutting Height	30-1290 mm				
	Reel Drive	Chain and Sprocket Hydraulic				
	Reel Height Adjustment					
	Feeder Housing	Chain Type Feed Rack 30-40				
	Reel RPM					
	FOR MAIZE					
	Cutter Bar Width	2210 mm (7.25 Feet) 4 610 mm				
	No. of Rows					
2015	Row Spacing					
E.	THRESHING MECHANISM					
E1.	Thresher Drum	WHEAT (RASP BAR	PAD (PEG T	35 5 1 mm - 1	MAIZE (RASP BAR)	
	Width (mm)	890	89	0	890	
	Diameter of Thresher Drum (mm)	605	60	5	605	
	Speed (rpm)	540-1200				
	Speed Adjustment	By means of Mechanical Variator				

E2.	CONCAVE					
	Length		790			
		Wheat	Front 17 mm, Rear 6-10 mm.			
	Clearance Paddy Maize		Front 17 mm, Rear 17 mm			
			Front 19 mm, Rear 19 mm			
	Adjustment		Mechanical			
E3.						
	Upper Sieve Are	ea	1.4 m ²			
	Lower Sieve Ar	ea	1.2 m ²			
E4.	STRAW WALKER					
	No. of Straw Wa	alker	4			
88	No. of Steps		4			
	Length (mm)		2500			
	Width		210			
F.	CAPACITIES					
	Grain Tank		1.7 m ³			
	Fuel Tank		160 ltr.			
G.	ELECTRICAL SYSTEM					
			12V, 100 Ah Battery starting, complete lighting			
			equipment, front and rear light			
H.	TYRE		Size	PLY RATING		
	Front		16.9 x 28	12pr		
-	Rear		7.50 x 16	12pr		
1.	MAIN DIMENSIONS (APPROX)					
			IN WORKING	IN TRANSPORT		
Length			7280 mm	10370 mm		
Width			3800 mm	2460 mm		
Height			3330 mm	3330 mm		
Ground Clearance			380 mm			
Total Weight			6460 Kg approx.			

Note: As per our policy is that of continuous development, specifications may change without any prior notice. For further details contact your nearest dealer.













PREET AGRO INDUSTRIES PVT. LTD.

Authorised Dealer :

Patiala Road, NABHA-147 201 (Pb.) INDIA.
Tel.: 01765-220400, 222609 | Toll Free : 1800-4190349
Email: sales@preetagro.com, info@preet.co