





www.preet.co

o f

For Latest Updates Follow us:

preettractorsofficial









BONNET









PREET 9049 4WD Center Gear

Technical Specifications

ENGINE						
Model / Make	PREET					
HP Category	95					
Туре	Four Stroke DI (Turbo Charged) with Inter cooler					
No. of Cylinders	4 Cylinder, Vertical Inline					
Bore / Stroke (mm)	105 / 118					
Rated Engine (RPM)	2200					
Displacement (cc)	4087					
Fuel Pump	Multicylinder Inline (BOSCH)					
Air Cleaner Type	Dry					
Cooling System	Water 0	Water Cooled				
CLUTCH						
Туре	Heavy Duty, Dry Type Dual Clutch					
Plate Size	Dia 280) mm, Cera	metalic F	riction		
TRANSMISSION						
Gear Box	8F + 2F	R Combinat	tion of Sli	ding & Co	nstant Mes	h
ROAD SPEED KM/hr	F	ORWAR	D	F	REVERSE	Ξ
Gear	HIGH	MEDIUM	LOW	HIGH	MEDIUM	LOW
1	11.45		2.91	16.03		4.07
2	15.07		3.58			
			5.93			
3	23.36		0.00			
3 4	23.36 36.88		9.36			
	36.88					
4	36.88	, ADDC				
4 HYDRAULIC SYSTEM	36.88 1	-				
4 HYDRAULIC SYSTEM Type	36.88 1 2 Lever Gear Ty	-				
4 HYDRAULIC SYSTEM Type Hydraulic Pump	36.88 1 2 Lever Gear Ty	/pe				
4 HYDRAULIC SYSTEM Type Hydraulic Pump Linkage	36.88 1 2 Lever Gear Ty TPL Ca	/pe				
4 HYDRAULIC SYSTEM Type Hydraulic Pump Linkage Lifting Capacity (kg)	36.88 1 2 Lever Gear Ty TPL Ca 2400	/pe				
4 HYDRAULIC SYSTEM Type Hydraulic Pump Linkage Lifting Capacity (kg) STEERING	36.88 1 2 Lever Gear Ty TPL Ca 2400	/pe tegory I-II				
4 HYDRAULIC SYSTEM Type Hydraulic Pump Linkage Lifting Capacity (kg) STEERING Type	36.88 2 Lever Gear Ty TPL Ca 2400 Power S	/pe tegory I-II	9.36	0		
4 HYDRAULIC SYSTEM Type Hydraulic Pump Linkage Lifting Capacity (kg) STEERING Type POWER TAKE OFF	36.88 2 Lever Gear Ty TPL Ca 2400 Power S	vpe tegory I-II Steering	9.36	0		

CAPACITIES (LITRES)				
Fuel Tank	67			
Engine Sump	11			
Cooling System	10			
Transmission & Hydraulic	55			
Steering System	2			
ELECTRICAL INSTALLA	ATION			
Battery	12V, 100Ah			
Alternator	12V, 42A			
Starter Motor	12V, 2.7 KW			
MIN. TURNING RADIUS	,			
Without Brakes (m)	3.75			
TYRE SIZE				
Front	12.4-24 R1			
Rear	18.4-30 R1			
Weight (Kg.)	2700			
FRONT DRIVE AXLE for	r 4WD Only			
Differential	Limited Slip			
Bevel Ratio	1:2.133			
Hub Ratio	1:6			
Total Ratio	1:12.8			
Diff. Oil Capacity (Ltr.)	5.5±10%			
Hub Oil Capacity (Ltr.)	0.6±15% each side			
BRAKES				
Type	Multi Disc Oil Immersed			
DIMENSIONS				
Overall Length	3900 mm			
Width	1950 mm			
Height upto Exhaust	2390 mm			
Ground Clearance	415 mm			
Wheel Base	2260 mm			
Front Track	1510 mm			
	1500			

Authorised Dealer

1580 mm

Rear Track

PREET TRACTORS PVT. LTD.

Head Office: Patiala Road, NABHA - 147201, (PB.) INDIA.

Email: info@preet.co | Visit us at: www.preet.co