Delivering Ultimate Mechanical Perfection.





Soyabean



Sunflower

Mustard

Ready to Thrill with eye catching Features :




Large grain tank capacity enables long working hours with minimum interruption



Comfortable cushioned driver seat with adjustable height




Hydraulic Power Steering easy to move with less force



Long length Straw Walker for complete exit of straw




Oil-immersed brake designed for use on a drive heavy machines



Bigger shields covering rotated parts with extra safety



Best Paint quality



Stainless steel sheet used for long life of auger casing



Heavy duty gearbox with five speeds Collar shift gears



Broader canopy providing extra cover to the operator area



Large sieve area for optimum grain cleaning



Ladder cover with sheet for safety purpose



Engine cooling by clean air through rotating sieve



Single Lever for shift gears



Heavy duty, long durable and robust structure makes our machine to withstand against any impact



Small Turning Radius



Broad Cutter Bar covering more cutting area. Superior tine material, Sharp edge cutting blade used, Auger with Big Dia



Cutting blade driven thru. Gear mechanism



Well designed crop feeding mechanism



Easy to open elevators for maintenance & services



Easy to turn in small area due to individual braking system



Long distance Focus Light



Stainless steel sheet used for long life of parts which are subjected to more wearing like elevators
Used UCF bearing is widely appreciated for durability and long serviceability

PREET 997 DELUXE SELF PROPELLED MULTICROP COMBINE HARVESTER

TECHNICAL SPECIFICATIONS

A.	ENGINE					
	Power	101 HP @ 2200 RPM				
	No. of Cylinders	Six				
	Air Cleaner	Dry				
	Cooling System	Water Cooled				
B.	CLUTCH					
	Type of Clutch	Single, Heavy Duty Dry Clutch				
	Dia	330 mm				
C.	TRANSMISSION	Access to the second se				
	No. of Gears	3 Forward, 1 Reverse 4 Forward, 1 Reverse		1 Reverse		
	Gear Speed (km/hr)					
-	Forward	L	Н	L	Н	
	1st Gear	2.3	3.7	1.8	2.9	
	2nd Gear	5.1	8.3	4	6.4	
	3rd Gear	12.8	20.5	7.25	11.6	
	4rd Gear		-	15.9	25.5	
	Reverse	5.7	8	5.3	8.4	
D.	CUTTER BAR MECHANISM	(For Wheat, Paddy &	Others)			
	Cutter Bar Width	4345 mm (14.25 Feet)				
	Cutting Height	65-1275 mm 58				
	No. of Blades					
	No. of Guards	29				
	Stroke	85 mm				
	Reel Speed	20-55 rpm				
	Reel Dia	915 mm				
	Feeder Housing	Chain Type Feed Rack				
	FOR MAIZE & SUNFLOWER					
	No. of Rows	5/6/7				
	Spacing of Rows	18"/24"/30"				
E.	THRESHING MECHANISM					
E1.	Thresher Drum	WHEAT	P/	ADDY	MAIZE	
		(RASP BAR	(PEG	TOOTH)	(RASP BAR)	
	Width (mm)	1250	1	250	1250	
	Diameter of Thresher Drum (mm)	605	(605	605	
	Cnood (rnm)	540-1200				
	Speed (rpm) Speed Adjustment	340-1200				

E2.	CONCAVE						
	Clearance	Wheat	Front 17 mm, Rear 6-10 mm.				
		Paddy	Front 17 mm, Rear 17 mm				
	Adjustment		Mechanical				
E3.	CLEANING SI	CLEANING SIEVES					
	Upper Sieve Are	ea	2.42 m ²				
	Lower Sieve Ar	ea	1.77 m ²				
E4.	STRAW WALKER						
	No. of Straw Wa	alker	5				
	No. of Steps		5				
	Length (mm)		3770				
-	Width		235				
F.	CAPACITIES						
	Grain Tank		2.5m³				
	Fuel Tank		365 ltr.				
G.	ELECTRICAL	ELECTRICAL SYSTEM					
	No. of Batteries	2	2				
	Capacity and ra	ting of each	12V, 100 ah				
H.	TYRE		Size	PLY RATING			
	Front		18.4 x 30	14pr			
	Rear		9.00 x 16	16pr			
I.	MAIN DIMENSIONS (APPROX)						
			IN WORKING	IN TRANSPORT			
Length		8370 mm	12450 mm				
Width		4665 mm	3035 mm				
Height		3850 mm 3850 mm					
Ground Clearance			370 mm				
Total Weight			9450 Kg approx.				

Note: As per our policy is that of continuous development, specifications may change without any prior notice. For further details contact your nearest dealer.



4949 TAF











Authorised Dealer :

PREET AGRO INDUSTRIES PVT. LTD.

Patiala Road, NABHA-147 201 (Pb.) INDIA. Tel.: 01765-220400, 222609 | Toll Free: 1800-4190349 Email: sales@preetagro.com, info@preet.co