

PREET 4949
HORNETT BSV



ALL NEW

**BUTTERFLY
OUTRIGGERS**



PREET BACKHOE LOADER
WITH THE MOST FUEL EFFICIENT & REMARKABLE PERFORMANCE



ENGINE New Generation Engine Complies with BS-V Norms with (ECU).
Output power & torque rise while offering exceptional fuel efficiency,
Environment Friendly & long life performance.

MODEL :	4R1190 Na1 BS-V (KIRLOSKAR)
Type	4 Stroke, DI, Diesel Engine
Fuel Pump Type	CRDI Type
High Idle Speed (rpm)	2335 ± 50
Horsepower @2200 rpm	Gross 74.5 hp (54.8 kW)
Max Torque @ 1300 rpm	305 Nm ± 5% (Gross)

TRANSMISSION / POWER TRAIN

CARRARO TRANSMISSION WITH SYNCHRO SHUTTLE & DIFFERENT GEAR OPTIONS WITH 4 SPEED (4 FORWARD & 4 REVERSE).

Transmission (Standard)	4F -4R Manual Power shift Transmission, Electrically actuated with twist grip.			
Gear Ratios	1st	F-1:5.603	1st	R-1:4.643
	2nd	F-1:3.481	2nd	R-1:2.884
	3rd	F-1:1.585	3rd	R-1:1.313
	4th	F-1:0.793	4th	R-1:0.657

AXLE

Front Axle	Heavy duty Steere Axle & Centre Pivot with Max. Angle
Rear Axle	Rigidly Mounted, Incorporates Carraro Max torque proportioning differential, driven by short propeller shaft.

BRAKE

Service Type :	Brake with Hyd. Actuated, Dual line oil immersed multi disc type wet brakes on the rear axle.
Parking Type :	Axle Mounted Spring applied Hydraulic Release

ELECTRICAL

Service Type :	12 volts/150 Ah with full Load lighting, Horn & reverse alarm.
Alternator Output	90 Amp.

HYDRAULICS

Pump Type	Tandem Pump which Provides great performance with fuel efficiency
Maximum Pump Capacity	54 cc / 118 Lpm (@ 2200 rpm)
System Pressure	220 Bar

STEERING

Type	Front Wheel Steering with Heavy Duty Double acting Cylinder system provides Equal turn with Quick Response.
------	---

TURNING CIRCLE

Outside Front Wheels (without brake)	8.85 mtr.
Outside Widest Loader Bucket (without brake)	11.6 mtr.
Outside Front Wheels (with brake)	7.3 mtr.
Outside Widest Loader Bucket (with brake)	9.6 mtr.

TYRE

Standard (Traction/ Industrial) Optional (Heavy Duty/HD)

Front	9.16 (16 PR)
Rear	16.9 -28 (12 PR) / 14-25 (20 PR)

SHIPPING WEIGHT

Gross Weight	7550 ± 100 kgs.
--------------	-----------------

SPEED

Gear	Forward km/hr	Reverse km/hr
1st	5.32	6.41
2nd	8.56	10.33
3rd	18.79	Not Recommended
4th	37.55	Not Recommended

(Above is with standard tyres)

SERVICE

Hydraulic System (Oil)	150 Ltrs.
Fuel Tank	120 Ltrs.
Engine Coolant	20 Ltrs.
Engine Oil	9.5 Ltrs.
Transmission	19 Ltrs.
Rear Axle	17 (14+3) Ltrs.

CABIN

Ergonomically designed cabin with contemporary styling, Tinted cab glasses provide better visibility and sun protection, Day & Night time visibility.

OPTIONAL FEATURES

Tele matic GPS SYSTEM (Global Positioning System)
Hydraulic Rock breaker Piping

HVAC Cabin
Heavy Duty Tyres

OPTIONAL ATTACHMENTS

6 in 1 loader bucket	1.1 CuM.
Excavator bucket	0.12 cu.m, 0.18 cu.m & 0.30 cu.m
Trench Bucket	0.06 cu.m, 0.09 cu.m, & 0.18 cu.m

STATIC DIMENSIONS




A Overall length	6.10 m
B Wheelbase	2.17 m
C Min. ground clearance	0.40 m
D Out rigger ground clearance	0.52 m
E Height to top of cab	3.00 m
F Width over bucket	2.33 m
G Overall height	3.63 m
H Track width - Front	1.89 m
I Track width - Rear	1.74 m/1.67 m
AR Rear over hang	1.78 m
AF Front over hang	2.24 m
Slew center to Rear Axle	1.35 m

EXCAVATOR DIMENSIONS

J Reach-ground level to slew center	5.74 m
K Max. width at outriggers	2.50 m
L Reach- ground level to rear wheel center	6.99 m
M Max. dig depth	4.80 m
N Max. working height	5.65 m
O Max. load over height	4.30 m
P Reach at full height to slew center	1.80 m
Q Bucket rotation	185°
Bucket Tear out Force	5700 kgf
Dipper Tear out force	3010 kgf
Lift Capacity to Bucket pivot at all reach	1470 kgf
Excavator Standard Bucket capacity	0.26 cu.m
Standard Bucket Width	0.79 m

LOADER DIMENSION

R Pin height	3.51 m
S Load over height	3.36 m
T Dump height	2.80 m
U Reach at ground	1.50 m
V Reach at full height bucket dumped	0.80 m
W Max. reach at full height	1.37 m
X Pin forward reach	0.47 m
Y Dump angle	53°
Z Rollback at ground	45°
Shovel Breakout force	6100 kgf
Loader arm Breakout force	5300 kgf
Standard Loader Bucket Capacity	1.1 cu.m
Pay load	1800 kgf



** Preet makes continuous improvements to all its products & reserved the right to change specification without any notice. Photo & illustrations may contain standard and optional equipment.

PREET CONSTRUCTION EQUIPMENTS PVT. LTD.

H.O. & Plant : Patiala Road, Nabha - 147 201 Punjab, India.

Ph.: +91-1765-220400, 222609

Email : info@preet.co | www.preet.co

Toll Free : 1800-419-0349



Authorized Dealer: