

Delivering Ultimate Mechanical Perfection.



FARMING WITH PASSION

PREET ROTAVATOR



Preet Rotavator manufactured & tested in the supervision of experienced engineers. Ultra-modern design of Rotavator is perfect for middle and heavy range tractors.

Benefits of Rotavator

- Like Harrow, Cultivator and Leveller, Preet Rotavator make the farm for sowing only once.
- Due to its Gear Drive facility, it is more powerful than chain drive rotavators.
- Rotavator reduces the fuel consumption and fatigue of tractor as well as it maintains the moisture in soil.
- Perform well in dry and moist land.
- Rotavator cuts the roots of the last crop in the fields and mixing them in the ground which works as organic manure.
- Rotavator is perfect implement for making the farm for sowing of Sugarcane, Paddy, Potatoes, Corn and Banana farming.
- Due to Special Design of Blades it reduces more fatigue of tractor and stop the slipping conditions. Reduces fuel consumption.

Main Features

- Life long quality High Tensile Blades.
- Export Quality Heavy Duty Gear Box.
- Rotavator frame made of high quality square type steel pipes.
- Nuts and Bolts made of high tensile blades.
- Safety Bolt installed in PTO Shaft for safety of Tractor and Rotavator.
- Side Disk available as per demand.
- Adjustable Trailing Board and Hitch Clamp for more grip on frame.



**24x7 Service
& Spare parts
facility available
in all states**



**Heavy Duty, Multi Speed
Gear Box**



Gear Drive



High Tensile Blades

Overall Size	0849	0749	0649	0549
Width	106.5" (2705 mm)	98" (2490 mm)	89.5" (2275 mm)	81" (2058 mm)
Tillage Width	92.5" (2350 mm)	84" (2135 mm)	75.5" (1918 mm)	67" (1702 mm)
Tillage Depth	6" (150 mm)	6" (150 mm)	6" (150 mm)	6" (150 mm)
Height	43" (1092 mm)	43" (1092 mm)	43" (1092 mm)	43" (1092 mm)
Length	53" (1345 mm)	53" (1345 mm)	53" (1345 mm)	53" (1345 mm)
HP Required	60-75 HP	50-60 HP	50-55 HP	40-45 HP
No. of Flange	11	10	9	8
No. of Blades	60	54	48	42
PTO Speed, RPM	540/1000	540/1000	540/1000	540/1000
Rotor Speed, RPM	215	215	215	215
Weight (Approx.)	525 Kg.	500 Kg.	475 Kg.	450 Kg.

Note: As our policy is that of continuous development, specifications may change without any prior notice. For further details contact your nearest dealer.

PREET AGRO INDUSTRIES PVT. LTD.

Patiala Road, NABHA-147 201 (Pb.) INDIA.

Tel.: 01765-220400, 222609 | Toll Free : 1800-4190349

Email: sales@preetagro.com, info@preet.co

Authorised Dealer :